

MICROFLEX®

SAFEGRIP®



BLUE
LATEX
NON-STERILE
AMBIDEXTROUS
FULLY TEXTURED
EXTENDED BEADED CUFF
FOR SINGLE USE ONLY

POWDER-FREE EXTENDED CUFF EXAMINATION GLOVES

SafeGrip® provides ideal protection for high-risk or heavy-duty conditions. Four times thicker than standard latex gloves, SafeGrip® provides unparalleled defense against many hazards in the work area.

- Meets or exceeds the emergency medical glove requirements of NFPA 1999, Standard on Protective Clothing for Emergency Medical operations, 2013 edition
- The thickest Microflex® glove in palm and finger
- Textured fingertips



| PRODUCT CODE | | PACKAGING | |
|--------------|-----------|-----------|------------|
| S | SG-375-S | 50 | Gloves/Box |
| M | SG-375-M | 10 | Boxes/Case |
| L | SG-375-L | | |
| XL | SG-375-XL | | |

| GLOVE PROFILE | | ASTM D 3578 | SAFEGRIP® |
|-----------------------|--------------|-----------------|-------------|
| Length | mm (inches) | min. 220 (8.7) | 295 (11.6) |
| Cuff Thickness | mm (mils) | n/a | 0.20 (7.9) |
| Palm Thickness | mm (mils) | min. 0.08 (3.1) | 0.28 (11.0) |
| Finger Thickness | mm (mils) | min. 0.08 (3.1) | 0.36 (14.2) |
| Tensile Strength | Before Aging | min. 18 | 34 |
| | After Aging | min. 14 | 28 |
| Elasticity/Elongation | Before Aging | min. 650 | 750 |
| | After Aging | min. 500 | 600 |
| Pinhole Defect Rate* | (AQL) | max. 2.5 | 1.5 |

* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED INDUSTRIES

Caution: This product contains natural rubber latex (latex) which may cause allergic reactions in some users. Safe use of this glove by or on latex sensitized individuals has not been established.