## MICR FLEX®

## ▲ TRANQUILITY<sup>®</sup>

## **POWDER-FREE EXAMINATION GLOVES**

WHITE NITRILE NON-STERILE AMBIDEXTROUS **TEXTURED FINGERS BEADED CUFF** FOR SINGLE USE ONLY NON-LATEX Tranquility<sup>®</sup> gloves are designed to deliver the perfect balance between protection and comfort. Along with superior strength, these nitrile gloves conform to the hand allowing for excellent tactile sensitivity and a secure grip. A compact storage box reduces space requirements in the office or lab.

- Compact box for reduced storage space
- Textured fingertips
- Non-stick properties resist tape and adhesives





## A LEADER IN DENTAL AND HEALTHCARE MARKETS

PRODUCT CODE		PACKAGING	
XS	TQ-601-XS	100	Gloves/Box
S	TQ-601-S	10	Boxes/Case
М	TQ-601-M		
L	TQ-601-L		
XL	TQ-601-XL		

GLOVE PROFILE		ASTM D 6319	TRANQUILITY®
Length	mm (inches)	min. 220 (8.7)	240 (9.5)
Cuff Thickness	mm (mils)	n/a	0.055 (2.2)
Palm Thickness	mm (mils)	min. 0.05 (2.0)	0.065 (2.6)
Finger Thickness	mm (mils)	min. 0.05 (2.0)	0.095 (3.7)
Tensile Strength	Before Aging After Aging	min. 14 min. 14	24 26
Elasticity/Elongation	Before Aging After Aging	min. 500 min. 400	500 400
Pinhole Defect Rate*	(AQL)	max. 2.5	1.5

\* Pinhole Defect Rate is FDA minimum requirement.



RECOMMENDED INDUSTRIES

® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2014 All Rights Reserved. COLL-SPEC-TO601. v1

